



Project:

Location:

Fixture Type:

Catalog Number:

AVAILABLE FINISHES:



Lanza

WS-52427

PRODUCT DESCRIPTION

Streamlined and simple. An elegant bar of organic Spanish Alabaster is mounted on a rectangular plate. When lit, this slim sconce offers luxurious, softly diffused illumination.

FEATURES


- ACLED driverless technology
- First class quality Spanish alabaster
- Natural alabaster with unique veining in each crafted piece
- Conversion plate included for 4" junction box
- Trimless spackle cover available for 4" square junction box recessed in drywall thicknesses of 1/2", 5/8", 1", and 1-1/4"; accessory not included and can be ordered separately (model# MKCP-3040-WT)
- 0-10V dimming option available (special order), unit dimensions: 3.4" x 1.2" x 0.5" (model#LDS065M010AFE-LO1)

SPECIFICATIONS

Rated Life	54000 Hours
Standards	ETL, cETL,Damp Location Listed,ADA
Input	120 VAC,50/60Hz
Dimming	ELV: 100-5%,TRIAC: 100-5%
Mounting	Can be mounted on wall in all orientations
Color Temp	3000K
CRI	90
Construction	Extruded aluminum body with alabaster shade

REPLACEMENT PARTS

RPL-GLA-52427 - Alabaster



Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS-52427 27"	3000K 3000K	AB Aged Brass BK Black	25.5W 25.5W	2318 2318	1281 1281

Example: **WS-52427-BK**

For custom requests please contact customs@modernforms.com



Project:

Location:

Fixture Type:

Catalog Number:

AVAILABLE FINISHES:



Lanza

WS-52434

PRODUCT DESCRIPTION

Streamlined and simple. An elegant bar of organic Spanish Alabaster is mounted on a rectangular plate. When lit, this slim sconce offers luxurious, softly diffused illumination.

FEATURES


- ACLED driverless technology
- First class quality Spanish alabaster
- Natural alabaster with unique veining in each crafted piece
- Conversion plate included for 4" junction box
- Trimless spackle cover available for 4" square junction box recessed in drywall thicknesses of 1/2", 5/8", 1", and 1-1/4"; accessory not included and can be ordered separately (model# MKCP-3040-WT)
- 0-10V dimming option available (special order), unit dimensions: 3.4" x 1.2" x 0.5" (model#LDS065M010AFE-LO1)

SPECIFICATIONS

Rated Life	54000 Hours
Standards	ETL, cETL,Damp Location Listed,ADA
Input	120 VAC,50/60Hz
Dimming	ELV: 100-5%,TRIAC: 100-5%
Mounting	Can be mounted on wall in all orientations
Color Temp	3000K
CRI	90
Construction	Extruded aluminum body with alabaster shade

REPLACEMENT PARTS

RPL-GLA-52434 - Alabaster



Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS-52434 34"	3000K 3000K	AB Aged Brass BK Black	38.8W 38.8W	3743 3743	1718 1718

Example: **WS-52434-BK**

For custom requests please contact customs@modernforms.com