



Project:

Location:

Fixture Type:

Catalog Number:

AVAILABLE FINISHES:



Draped

WS-W60412

PRODUCT DESCRIPTION


Dark and light. A solid block of cast glass held by a substantial linear frame radiates clean LED illumination to the surrounding night.

FEATURES

- ACLED driverless technology
- Downward illumination
- Solid block of cast glass
- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- Option to pre-select color temperature or adjust in the field
- 0-10V dimming option available (special order), unit dimensions: 3.4" x 1.2" x 0.5" (model#LDS065M010AFE-LO1)

SPECIFICATIONS

| | |
|---------------------|--|
| Rated Life | 54000 Hours |
| Standards | ETL, cETL, Wet Location Listed, IP65, ADA |
| Input | 120 VAC, 50/60Hz |
| Dimming | ELV: 100-5%, TRIAC: 100-5% |
| Mounting | Can be mounted on wall vertically or upside down |
| Color Temp | 3500K, 4000K, 2700K, 3000K |
| CRI | 90 |
| Construction | Extruded aluminum body with cast glass diffuser |




WS-W60412

| Model & Size | Color Temp | Finish | LED Watts | LED Lumens | Delivered Lumens |
|---------------|------------|----------|-----------|------------|------------------|
| WS-W60412 12" | 2700K | BK Black | 15.9W | 1350 | 552 |
| | 3000K | BK Black | 15.9W | 1350 | 552 |
| | 3500K | BK Black | 15.9W | 1350 | 552 |
| | 4000K | BK Black | 15.9W | 1350 | 552 |

Example: **WS-W60412-40-BK**

For custom requests please contact customs@modernforms.com



WS-W60418

Project:

Location:

Fixture Type:

Catalog Number:

AVAILABLE FINISHES:



Draped

WS-W60418

PRODUCT DESCRIPTION

Dark and light. A solid block of cast glass held by a substantial linear frame radiates clean LED illumination to the surrounding night.

FEATURES

- ACLED driverless technology
- Downward illumination
- Solid block of cast glass
- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- Option to pre-select color temperature or adjust in the field
- 0-10V dimming option available (special order), unit dimensions: 3.4" x 1.2" x 0.5" (model#LDS065M010AFE-LO1)

SPECIFICATIONS

| | |
|--------------|--|
| Rated Life | 54000 Hours |
| Standards | ETL, cETL,Wet Location Listed,IP65,ADA |
| Input | 120 VAC,50/60Hz |
| Dimming | ELV: 100-5%,TRIAC: 100-5% |
| Mounting | Can be mounted on wall vertically or upside down |
| Color Temp | 3500K,3000K,2700K,4000K |
| CRI | 90 |
| Construction | Extruded aluminum body with cast glass diffuser |

| Model & Size | Color Temp | Finish | LED Watts | LED Lumens | Delivered Lumens |
|---------------|------------|----------|-----------|------------|------------------|
| WS-W60418 18" | 2700K | BK Black | 16.4W | 1350 | 511 |
| | 3000K | BK Black | 16.4W | 1350 | 511 |
| | 3500K | BK Black | 16.4W | 1350 | 511 |
| | 4000K | BK Black | 16.4W | 1350 | 511 |

Example: **WS-W60418-40-BK**

For custom requests please contact customs@modernforms.com