

PD-78014L

Project: _____

Location: _____

Fixture Type: _____

Catalog Number: _____

AVAILABLE FINISHES:



Minx

PD-78014L

PRODUCT DESCRIPTION

Artisanally sparkling pendants are installed in various arrangements to create an artful statement as well as deliver ample lighting to spaces throughout a home or business.

FEATURES

- Driver concealed within the canopy
- Artisanal reclaimed K5 crystal shade
- Thin powered aircraft cables provide an ultra clean look for adjustable suspension height
- NEC CODE (314.24) requires that ceiling outlet boxes in the U.S. support up to 50 lbs.
- This fixture in the 14 and 23 light format exceeds 50 lbs. and must be installed using a U.L. listed outlet box approved for up to 75 lbs. and 100 lbs. or supported independently of the outlet box

SPECIFICATIONS

Rated Life	55000 Hours
Standards	ETL, cETL,Damp Location Listed
Input	120-277V,50/60Hz
Dimming	ELV, 0-10V, TRIAC
Color Temp	3000K
CRI	90
Construction	Steel body with K5 crystal fused acrylic


REPLACEMENT PARTS

RPL-GLA-78013 - Inner glass

Model & Size	Color Temp & CRI	Watt	Lumens	Finish
PD-78014L 40" - 14 Lights	3000K 90 3000K 90	67W 67W	3387 3387	AB Aged Brass AN Antique Nickel

Example: **PD-78014L-AN**

For custom requests please contact customs@modernforms.com



PD-78023L

Project:

Location:

Fixture Type:

Catalog Number:

AVAILABLE FINISHES:



Minx

PD-78023L

PRODUCT DESCRIPTION

Artisanally sparkling pendants are installed in various arrangements to create an artful statement as well as deliver ample lighting to spaces throughout a home or business.

FEATURES

- Driver concealed within the canopy
- Artisanal reclaimed K5 crystal shade
- Thin powered aircraft cables provide an ultra clean look for adjustable suspension height
- NEC CODE (314.24) requires that ceiling outlet boxes in the U.S. support up to 50 lbs.
- This fixture in the 14 and 23 light format exceeds 50 lbs. and must be installed using a U.L. listed outlet box approved for up to 75 lbs. and 100 lbs. or supported independently of the outlet box

SPECIFICATIONS

Rated Life	55000 Hours
Standards	ETL, cETL,Damp Location Listed
Input	120-277V,50/60Hz
Dimming	ELV, 0-10V, TRIAC
Color Temp	3000K
CRI	90
Construction	Steel body with K5 crystal fused acrylic

REPLACEMENT PARTS

RPL-GLA-78013 - Inner glass

Model & Size	Color Temp & CRI	Watt	Lumens	Finish
PD-78023L 54" - 23 Lights	3000K 90 3000K 90	110W 110W	5565 5565	AB Aged Brass AN Antique Nickel

Example: **PD-78023L-AN**

For custom requests please contact customs@modernforms.com