

INSTALLATION INSTRUCTIONS

Item# 1419-897

READ AND SAVE THESE INSTRUCTIONS

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.
VERTISEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.

ASSEMBLING THE FIXTURE (Fig.1&2)

1. Shut off power at the fuse box or circuit breaker box and remove the old fixture including the mounting hardware.
2. Carefully unpack your new fixture and lay out all the parts in a clean area. Ensure not to misplace any small part necessary for installation.
3. Thread all thread (D) into crossbar (A) by using washer and hex nut provided. Note: The length of all thread (D) into crossbar (A) maybe adjusted if necessary.
4. Take the crossbar assembly and mount to junction box (JB) (*not provided*) with #8-32 junction box screws (C). The side of crossbar (A) marked "GND" must be face out.

HANGING THE FIXTURE (Fig.1&2)

5. When assembling the main body, there will be one set of parts that have the supply wire laced through.
6. Determine the desired hanging height and thread rods (H/I) onto coupler of fixture body.
7. Secure swivel (G) onto the rods (H/I) and place the canopy (F) over the other end of the swivel (G), follow by support cable and then secure with washer & hex nut provided.
8. The support cable (SC) is provided to support the weight of the fixture while wiring. Align the fixture to crossbar (A) and attach hook (HK) on the end of support cable (SC) into a slot located on crossbar (A). Carefully allow the support cable (SC) to support the weight of the fixture while wiring.

CONNECTING THE WIRE (Fig. 3)

9. Connect the electrical wire as shown in Fig. 3, making sure that all the wire connectors are secured. If your junction box has a ground wire (green, or bare copper), connect fixture's ground wire to it. Otherwise, connect fixture's ground wire directly to crossbar (A) using green screw provided.
10. Tuck wire connections neatly into junction box (JB).
11. To mount the fixture to the ceiling, first slip all thread (D) through the mounting holes (I) in the canopy (F) and secure with finial (J). (Fig. 2)

FINISHING THE FIXTURE (Fig. 1)

12. Install (10) ten candelabra base bulbs (K) up to 60 watts each or CFL or LED equivalent (not included) in accordance with the fixture specifications.

DO NOT EXCEED THE MAXIMUM WATTAGE RATING!
(NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!)

Your installation is now complete. You can now turn the power ON and test the fixture.

Note: Illustration (Fig. 1) on this manual is for installation purposes only. It may or may not be identical to the fixture purchased.

