

# INSTALLATION INSTRUCTIONS

Item# 10388-732

## READ AND SAVE THESE INSTRUCTIONS

**WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.**

**AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.**

1. Shut off power at the fuse box or circuit breaker box and remove the old fixture including the mounting hardware.

2. Carefully unpack your new fixture and lay out all the parts in a clean area. Take care not to misplace any small parts necessary for installation.

### ASSEMBLING THE FIXTURE (Fig.1)

3. Screw four decorative rods (O) onto the fixture body (P). and place the top of decorative rods (O) over the coupling (N) and secure it by using washer (M) and hex nut (L). Screw column coupling (K) onto all thread of the coupling (N).

4. Determine desired hanging height and thread rods (J/I) on column coupling (K). Pass wires carefully through each rod as you assemble.

5. Push fixture wires carefully through the swivel (G), screw collar ring (H), canopy(F) and nipple(C) of crossbar assembly. Thread swivel (G) to rod (J/I).

5. Slip screw collar ring (H) and canopy (F) over swivel (G) and allow them to rest on rod (J/I). Thread swivel (G) to nipple(C) of crossbar assembly.

6. Attach crossbar assembly to junction box (not included) using junction box screw (E). The side of crossbar (A) marked "GND" must face out. The length of nipple (C) into crossbar (A) maybe adjusted if necessary. Then tighten with lock nuts (D) provided. Push fixture wires through nipple (C) inside junction box.

### CONNECTING THE WIRES (Fig. 2)

7. Connect electrical wires as shown in Fig.2, making sure that all wire connectors are secured. If your junction box has a ground wire (green or bare copper), connect the fixture's ground wire to it. Otherwise, connect the ground wire directly to the crossbar (A) using the green screw (B) provided.

8. Tuck wire connectors neatly into the junction box.

### COMPLETING THE INSTALLATION (Fig. 1)

9. Position canopy (F) up against ceiling and thread screw collar ring (H) to secure fixture to ceiling.

10. Install (8) eight candelabra base bulbs (Q) up to 60 watts each or CFL or LED equivalent (not included) in accordance with the fixture specification.—**DO NOT EXCEED THE MAXIMUM WATTAGE RATING! (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!).**

11. Screw glass shade (R) over the socket in the fixture body (P). Do not over tighten.

Your installation is now complete. Return power to the junction box and test the fixture.

**Note:** Illustration (Fig. 1) on this manual is for installation purposes only. It may or may not be identical to the fixture purchased.

**IMPORTANT: FIXTURE SHOULD BE INSTALLED BY A QUALIFIED ELECTRICIAN TO ENSURE PROPER WIRING**

Fig.1

Set#A-018B

-Crossbar

-Ground Screw

-Junction Box Screw\*2

Rod#W35-H-732(I-6")

W35-1-732 X 3 (J-12")




Fig. 2

FIXTURE WIRES  
Black or  
Smooth



HOUSE WIRES  
Black  
(Hot)

FIXTURE WIRES  
White or  
Ribbed



HOUSE WIRES  
White  
(Neutral)

FIXTURE WIRES  
Bare  
Copper  
(Ground)




HOUSE WIRES  
Green  
(Ground)




american  
lighting  
association

**Fig.3**



**a. Hardware Bag:**

- A. Crossbar\*1
- B. Ground screw\*1
- C. Nipple \*1
- D. Lock nut\*3
- E. Junction Box Screw\*2
- F. Canopy \*1
- G. Swivel\*1
- H. Screw collar ring\*1



**b. Hardware Bag:**

- J. ROD 12"\*3
- I. ROD 6"\*1

