



PIPELINE CM7 – C/W

CEILING/WALL / DESIGNER: CAINE HEINTZMAN / 2021

A-N-D

MANUFACTURED IN CANADA

A-N-D.COM



PIP-CM7-CW-BK-27-ELV-120

VISIT [A-N-D.COM](https://www.a-n-d.com) FOR 3D MODELS INCLUDING REVIT/IES.

DESCRIPTION

Space efficient, the surface mounted Pipeline provides accent lighting while becoming an integral element of the environment it is set in.

TYPE

Ceiling/Wall

DIMENSIONS

- Luminaire: 267 x 26 x 9cm / 105" x 10" x 3.5"

POWER TRIM OPTIONS

- Trimless (Mud-in or surface mount, remote power supply)

* SEE INSTALL INSTRUCTIONS

CERTIFICATIONS




* APPLICATION: DRY INDOOR LOCATION ONLY


TECHNICAL INFORMATION

- Input Voltage: 110–120V, 220–240V, 110–277V
- Lamping: Integral 68W 24V DC LED CRI 90+, 50,000 hours
- Lumens: 2864 lumens delivered
- Power Supply: Phase dimming, 0-10V, DALI

COLOUR TEMPERATURE OPTIONS



DIM TO WARM



MATERIALS

- Aluminum
- Acrylic

FINISHES



BLACK "BK"



WHITE "WH"



BRASS "BR"



COPPER "CP"



CHROME "CH"



FOR CUSTOM FINISHES, PLEASE INQUIRE.

SERIES	SIZE	TYPE	BODY FINISH	END CAP/ JOINER/ELBOWS	CCT	PS	VOLTAGE IN
PIP	CM7	CW	<input type="checkbox"/> BK (BLACK) <input type="checkbox"/> WH (WHITE)	<input type="checkbox"/> BK (BLACK) <input type="checkbox"/> WH (WHITE)	<input type="checkbox"/> 27 (2700K) <input type="checkbox"/> 30 (3000K) <input type="checkbox"/> 35 (3500K) <input type="checkbox"/> 41 (4100K) <input type="checkbox"/> DW (DIM TO WARM)	<input type="checkbox"/> ELV <input type="checkbox"/> 010 <input type="checkbox"/> DAL	<input type="checkbox"/> 120 <input type="checkbox"/> 230 <input type="checkbox"/> 277*
			<input type="checkbox"/> BR (BRASS) <input type="checkbox"/> CP (COPPER) <input type="checkbox"/> CH (CHROME)	<input type="checkbox"/> BR (BRASS) <input type="checkbox"/> CP (COPPER) <input type="checkbox"/> CH (CHROME)			

*277 ONLY AVAILABLE WITH 010

