



Photo: PHS-BBR-03

Phase. Chandelier

Inspired by the exquisite balancing act found in hanging kinetic mobiles. Phase light is an interpretation of a circle in three forms: a sphere, a disc, and a melted semi-circle. This vertical fixture is built from the bottom up to stay balanced. Every component of each tier is hand finished and weighted precisely before being attached to the arm. Each tier acts as a predictably weighted foundation for the tier above, where the process repeats. Phase conceals its wires inside the arms while maintaining perfect parallel line structures. Rather than relying on adjustable parts—which shift over time and alter the geometry of the fixture—Phase achieves a fixed equilibrium with weight and steel piping.

Item Code

PHS		03	
Model	Finish	Chandelier	Temperature


Model PHS Phase		Dimension Ø5ft - 6ft Ø1.5m - 1.8m	Canopy Dimension Ø8in X H1.25in Ø200mm X H32mm	Dimming A. ELV B. 0-10V Extra	Input Voltage 120V 50/60Hz
Finish BBR Brushed Brass BABR Brushed Antique Brass OBK Black Oxide CUS Custom		Material Steel Aluminum Plexiglass Glass	Weight 15lbs 6.8kg	Driver Integral in Canopy	Output Voltage 12V
Chandelier 03 Chandelier		Mounting J-Box	Temperature 2200K 2700K 3000K 3500K	Lamping 90CRI 6W 690lm	Certification CE Compliant Damp Rated 
Due to the length of tiers, a natural arc occurs on the longest tier					
Lamp Life 15,000 hours					



Photo: PHS-BABR-03

Phase. Chandelier

Inspired by the exquisite balancing act found in hanging kinetic mobiles, Phase light is an interpretation of a circle in three forms: a sphere, a disc, and a melted semi-circle. This vertical fixture is built from the bottom up to stay balanced. Every component of each tier is hand finished and weighted precisely before being attached to the arm. Each tier acts as a predictably weighted foundation for the tier above, where the process repeats. Phase conceals its wires inside the arms while maintaining perfect parallel line structures. Rather than relying on adjustable parts—which shift over time and alter the geometry of the fixture—Phase achieves a fixed equilibrium with weight and steel piping.

Item Code

PHS		03	
Model	Finish	Chandelier	Temperature


Model PHS Phase		Dimension Ø5ft - 6ft Ø1.5m - 1.8m	Canopy Dimension Ø8in X H1.25in Ø200mm X H32mm	Dimming A. ELV B. 0-10V Extra	Input Voltage 120V 50/60Hz
Finish BBR Brushed Brass BABR Brushed Antique Brass OBK Black Oxide CUS Custom		Material Steel Aluminum Plexiglass Glass	Weight 15lbs 6.8kg	Driver Integral in Canopy	Output Voltage 12V
Chandelier 03 Chandelier		Mounting J-Box	Temperature 2200K 2700K 3000K 3500K	Lamping 90CRI 6W 690lm	Certification CE Compliant Damp Rated 
Due to the length of tiers, a natural arc occurs on the longest tier					
				Lamp Life 15,000 hours	



Photo: PHS-OBK-03

Phase. Chandelier

Inspired by the exquisite balancing act found in hanging kinetic mobiles. Phase light is an interpretation of a circle in three forms: a sphere, a disc, and a melted semi-circle. This vertical fixture is built from the bottom up to stay balanced. Every component of each tier is hand finished and weighted precisely before being attached to the arm. Each tier acts as a predictably weighted foundation for the tier above, where the process repeats. Phase conceals its wires inside the arms while maintaining perfect parallel line structures. Rather than relying on adjustable parts—which shift over time and alter the geometry of the fixture—Phase achieves a fixed equilibrium with weight and steel piping.

Item Code

PHS		O3	
Model	Finish	Chandelier	Temperature


Model PHS Phase		Dimension Ø5ft - 6ft Ø1.5m - 1.8m	Canopy Dimension Ø8in X H1.25in Ø200mm X H32mm	Dimming A. ELV B. 0-10V Extra	Input Voltage 120V 50/60Hz
Finish BBR Brushed Brass BABR Brushed Antique Brass OBK Black Oxide CUS Custom		Material Steel Aluminum Plexiglass Glass	Weight 15lbs 6.8kg	Driver Integral in Canopy	Output Voltage 12V
Chandelier O3 Chandelier		Mounting J-Box	Temperature 2200K 2700K 3000K 3500K	Lamping 90CRI 6W 690lm	Certification CE Compliant Damp Rated 
Due to the length of tiers, a natural arc occurs on the longest tier					
Lamp Life 15,000 hours					



Photo: PHS-BABR-01

Phase. Chandelier

Inspired by the exquisite balancing act found in hanging kinetic mobiles, Phase light is an interpretation of a circle in three forms: a sphere, a disc, and a melted semi-circle. This vertical fixture is built from the bottom up to stay balanced. Every component of each tier is hand finished and weighted precisely before being attached to the arm. Each tier acts as a predictably weighted foundation for the tier above, where the process repeats. Phase conceals its wires inside the arms while maintaining perfect parallel line structures. Rather than relying on adjustable parts—which shift over time and alter the geometry of the fixture—Phase achieves a fixed equilibrium with weight and steel piping.

Item Code

PHS		01	
Model	Finish	Chandelier	Temperature


Model PHS	Phase	Dimension W38.25in W972mm	Canopy Dimension Ø5in X H1.1875in Ø130 X H30mm	Dimming A. ELV B. 0-10V Extra	Input Voltage 120V 50/60Hz
Finish BBR BABR OBK CUS	Brushed Brass Brushed Antique Brass Black Oxide Custom	Material Steel Aluminum Plexiglass Glass	Weight 7lbs 6.8kg	Driver Integral in Canopy	Output Voltage 12V
Chandelier 01	Chandelier	Mounting J-Box	Temperature 2200K 2700K 3000K 3500K	Lamping 90CRI 2W 230lm	Certification CE Compliant Damp Rated 
				Lamp Life 15,000 hours	



Photo: PHS-BBR-01

Phase. Chandelier

Inspired by the exquisite balancing act found in hanging kinetic mobiles, Phase light is an interpretation of a circle in three forms: a sphere, a disc, and a melted semi-circle. This vertical fixture is built from the bottom up to stay balanced. Every component of each tier is hand finished and weighted precisely before being attached to the arm. Each tier acts as a predictably weighted foundation for the tier above, where the process repeats. Phase conceals its wires inside the arms while maintaining perfect parallel line structures. Rather than relying on adjustable parts—which shift over time and alter the geometry of the fixture—Phase achieves a fixed equilibrium with weight and steel piping.

Item Code

PHS		01	
Model	Finish	Chandelier	Temperature


Model PHS Phase		Dimension W38.25in W972mm	Canopy Dimension Ø5in X H1.1875in Ø130 X H30mm	Dimming A. ELV B. 0-10V Extra	Input Voltage 120V 50/60Hz
Finish BBR Brushed Brass BABR Brushed Antique Brass OBK Black Oxide CUS Custom		Material Steel Aluminum Plexiglass Glass	Weight 7lbs 6.8kg	Driver Integral in Canopy	Output Voltage 12V
Chandelier 01 Chandelier		Mounting J-Box	Temperature 2200K 2700K 3000K 3500K	Lamping 90CRI 2W 230lm	Certification CE Compliant Damp Rated 
				Lamp Life 15,000 hours	




Photo: PHS-OBK-01

Phase. Chandelier

Inspired by the exquisite balancing act found in hanging kinetic mobiles, Phase light is an interpretation of a circle in three forms: a sphere, a disc, and a melted semi-circle. This vertical fixture is built from the bottom up to stay balanced. Every component of each tier is hand finished and weighted precisely before being attached to the arm. Each tier acts as a predictably weighted foundation for the tier above, where the process repeats. Phase conceals its wires inside the arms while maintaining perfect parallel line structures. Rather than relying on adjustable parts—which shift over time and alter the geometry of the fixture—Phase achieves a fixed equilibrium with weight and steel piping.

Item Code

PHS		01	
Model	Finish	Chandelier	Temperature

Model PHS Phase		Dimension W38.25in W972mm	Canopy Dimension Ø5in X H1.1875in Ø130 X H30mm	Dimming A. ELV B. 0-10V Extra	Input Voltage 120V 50/60Hz
Finish BBR Brushed Brass BABR Brushed Antique Brass OBK Black Oxide CUS Custom		Material Steel Aluminum Plexiglass Glass	Weight 7lbs 6.8kg	Driver Integral in Canopy	Output Voltage 12V
Chandelier 01 Chandelier		Mounting J-Box	Temperature 2200K 2700K 3000K 3500K	Lamping 90CRI 2W 230lm	Certification CE Compliant Damp Rated 
				Lamp Life 15,000 hours	