

# FLOS

F1310U00 Primer

## Camouflage 140 mm Primer


Designed by Piero Lissoni



24V remote power supply to be ordered separately. Includes power cable of 100 mm. The power supply can be installed remotely (installation box not required) or housed at the back of the luminaire in the optional installation box.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



\*Concrete, crema d'orcio, basaltina H = 1.38"

### Main specifications

Mounting	Wall surface
Environments	Outdoor wet location
LED type	Power LED
Lamp category	LED
Power (W)	8
Source flux (lm)	786
System flux (lm)	474

### Physical

Color	Primer
Orientation	Fixed
Length (in)	5.5
Net weight (lb)	1.1
Package height (in)	3.9
Package width (in)	7.87
Package length (in)	7.87
Package volume (in)	244
IP internal	65

### Download

Family spec sheet [ZIP](#)  
Mounting instructions [ZIP](#)

### Photometric Files


LDT / IES [ZIP](#)

### Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	80
Beam angle C0-180 (°)	157
Beam angle C90-270 (°)	157

Electrical

Driver	Remote excluded
Dimmable	No
Dimming type	Non Dimmable, Dimmable 1-10V, Dimmable DALI 1

Notes

We recommend using a connection system with a degree of protection greater than or equal to the degree of protection of the luminaire.

During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the coating.

For LED fixtures, there is evidence that most of the damages are connected to electrical effects related to the insulations, which cause destructive electrical discharges

These effects are frequently caused by:

- over voltage coming from the mains’ network where fixture is connected.
- electrostatic discharge (ESD) coming from the environment.

The use of a protective device against the overvoltage on the electrical installation is warmly suggest this helps to reduce the intensity of some of these phenomenon and prevent irreversible damages. The selection of the type of device to be used must be adjust on the electrical plant.

Accessories & Power Supply



REQUIRED  
Power supply

Electrical

LED40W24V-PWM-B01  
LED power supply source for  
remote installation, 24V/40W  
Dimming 0-10V



REQUIRED  
Power supply

Electrical

LED60W24V-PWM-B01  
LED power supply source for  
remote installation, 24V/60W,  
120-277V, Dimming 0-10V



REQUIRED  
Power supply

Electrical

LEDSB96W24V-VAR-Y01  
LED power supply source for  
remote installation, 24V/96W,  
120-277V, Variable dim Triac, 0-  
10V Dimming PWM