



Roll & Hill

Surface Mount

<p><u>Series</u> Pearl</p> <p><u>Product</u> Surface Mount</p> <p><u>Dimensions</u> L 11in/27.9cm x W 11in/27.9cm H 7.3in/18.6cm</p> <p><u>Weight</u> 10.5lb/4.8kg Weight may vary by glass</p> <p><u>Materials</u> Brass, Glass</p>	<p><u>Finishes/Colors</u> Oil Rubbed Bronze, Brass</p> <p><u>Glass Color</u> Peach, Fume, Cased Peach, Cased Fume</p> <p><u>Diffuser</u> Opal</p> <p><u>Canopy</u> 5.25-inch round in matching metal finish</p> <p><u>Driver location</u> Driver located in canopy</p> <p><u>Fixture Mounting</u> Designed to be mounted on standard 4in. Electrical Box. Two #8-32 screws included. Additional mounting hardware provided for 240V versions.</p> <p><u>Certifications</u> UL, cUL (120V) CE (240V)</p>	<p><u>120/277V Illumination</u> Integrated LED Wattage: 11W Lumens (Peach): 450 Lumens est. Lumens (Fume): 450 Lumens est. Lumens (Cased Peach): 350 Lumens est. Lumens (Cased Fume): 300 Lumens est. Color Temperature: 2700K, 90+ CRI LED Lifetime: 50,000 Hours est. Dimming: 120V - TRIAC, ELV, 0-10V 277V - 0-10V only</p> <p><u>240V Illumination</u> Integrated LED Wattage: 11W Lumens (Peach): 450 Lumens est. Lumens (Fume): 450 Lumens est. Lumens (Cased Peach): 350 Lumens est. Lumens (Cased Fume): 300 Lumens est. Color Temperature: 2700K, 90+ CRI LED Lifetime: 50,000 Hours est. Dimming: 0-10V (DALI dimming available upon request)</p>
--	---	--