



# Glyph

Sconces

## YOUR PRODUCT CODE

GY- - - - -

### DESCRIPTION

Designed in collaboration with the acclaimed Yabu Pushelberg studio, our newest Glyph sconce embraces the gestural simplicity of glyphs—symbols that compact meaning into a minimal graphic form. The collaborative design comprises two vertical panels joined at 90 degrees that form two halves of a whole—an intersection of contrasting colors and textures, as well as distinct shadows that complement a soft diffusion of light.

### MATERIALS

Aluminum sheet, plastic diffuser, metallic powder coat aluminum base.

### PRODUCT DIMENSIONS

9 W x 14 H x 3.7 in D

### PRODUCT WEIGHT

4.5 lbs / 2 kg

### PERFORMANCE

Delivered Lumens 186.7 lm  
Power Consumption 7W  
Luminous Efficacy 26.1 lm  
90 CRI

### PATENT FILE NUMBER

Patent Number 202411594, DM/236891

### CERTIFICATION

ADA Compliant  
UL Listed  
• Suitable for Damp Locations  
IP65



### LED LIFESPAN

50k hours

## SPECIFICATION LOGIC

### PRIMARY FINISH

Luster	PC93
Emerald	PC28
Glimmer	PC32
Custom Powder Coated	PCXX

### COLOR TEMPERATURE

2700K (warm white)	27
3000K (soft white)	30
3500K (neutral white)	35

### DIMMING / CONTROL / INPUT

10% Dimming, TRIAC / Forward Phase Control, 120V Input	10_TRIAC_120V
1% Dimming, 0-10V Control, 120V or 277V "Universal Input" (Driver External)	1_10V_UNV
1% Dimming, TRIAC / Forward Phase Control, 120V Input (Driver External)	1_TRIAC_120V
0.1% Dimming, 0-10V Control, 120V or 277V "Universal Input" (Driver External)	0.1_10V_UNV
Low Voltage (Driver required, driver not included)	LV

### IP RATING

IP 65	IP65
-------	------

## DRAWINGS

GY Glyph Sconce

