

Technical data

| | |
|-------------------------------|--------------------|
| Rated voltage | 120V AC |
| Input voltage range | 110-120V AC |
| Driver output | - |
| Alimentation output | - |
| Class | 1 |
| IP | 44 |
| IK | 10 |
| Diffuser | Opal polycarbonate |
| Bulb cover | No |
| Source | E26 |
| Color temperature real output | - |
| Real light output | - lm |
| Total consupcion | - W |
| Energy class | - |
| Luminous efficacy | - |
| IRC | - |
| SDCM | - |
| Optic | - |
| Dimmable | - |
| Ta | - |
| Led lifetime | - |
| Ambient temperature range | -10 ~50°C |
| UGR | - |
| ULR | - |
| THDI | - |
| Fixing kit | No |
| With sensor | No |
| With IP55 socket | No |

[Download the installation manual](#)



Dallas

catalogue 2020 p. 40

ref. PE119001001

EAN. 3663660271813

Model ①



Materials and finishes

| | |
|----------|-------------|
| Material | aluminium |
| Colour | White - 001 |

Logistic data

| | |
|----------------------|-------------------|
| Product dimensions | H.509 L.320 P.506 |
| Net weight | 0.000 Kg |
| Gross weight | 0.000 Kg |
| Package dimensions 1 | H.580 L.340 P.340 |

Certifications and warranties

| | |
|----------------|------------------------|
| CE | Pour fiche Média |
| UL | Yes |
| EAC | No |
| RoHS | No |
| ENEC | No |
| Anti-corrosion | 25 years (on Aluminum) |
| Technical | 5 years |
| Electronics | 5 years |