

Technical data

| | |
|-------------------------------|----------------------------------|
| Rated voltage | 120V AC |
| Input voltage range | 110-120V AC |
| Driver output | - |
| Class | 1 |
| IP | 65 |
| IK | - |
| Diffuser | Clear PMMA |
| Bulb cover | - |
| Source | E26 |
| Color temperature real output | - |
| Real light output | - lm |
| Total consumption | - W |
| Energy class | Classe de la lampe (non fournie) |
| Luminous efficacy | - |
| IRC | - |
| SDCM | - |
| Optic | - |
| Dimmable | - |
| Ta | - |
| Ambient temperature range | -10 ~50°C |
| UGR | - |
| ULR | - |
| THDI | - |
| Fixing kit | Yes |
| With sensor | No |
| With IP55 socket | No |

[Download the installation manual](#)

Materials and finishes

| | |
|----------|---------------------|
| Material | aluminium |
| Colour | British green - 019 |

Logistic data

| | |
|----------------------|-------------------|
| Product dimensions | H.705 L.220 P.220 |
| Net weight | 2.090 Kg |
| Gross weight | 2.800 Kg |
| Package dimensions 1 | H.480 L.250 P.250 |

Certifications and warranties

| | |
|----------------|------------------------|
| CE | Pour fiche Média |
| UL | Yes |
| EAC | No |
| RoHS | No |
| ENEC | No |
| Anti-corrosion | 25 years (on Aluminum) |
| Technical | 5 years |
| Electronics | 5 years |