Amelie Wall

CV1061, CV1071, CV1081 1.0

VISUAL COMFORT & CO.

STUDIO COLLECTION

GENERAL PRODUCT INFORMATION:

These fixtures are intended to be installed utilizing NEC compliant junction boxes. **Must use 2"x4" junction box (backplate 2.5"W)**

This product is safety listed for damp locations.

This product may be dimmed with a LED dimmer.

Fixture may be mounted horizontal or vertical.

This instruction shows a typical installation.

CAUTION - RISK OF FIRE

This product must be installed in accordance with the applicable installation code by a person familiar with the construction and operation of the product and the hazards involved.

Use minimum 90°C supply conductors.

SAVE THESE INSTRUCTIONS!





VISUAL COMFORT & CO.

7400 Linder Ave., Skokie, IL 60077 T 847.410.4400 | F 847.410.4500 www.visualcomfort.com

Install the Fixture



- 1 Temporarily install the mounting plate to the junction box.
- 2 Mark the anchor locations through holes on the mounting plate. Remove the mounting plate.
- 3 Drill appropriate sized holes at the marked locations and install the anchors.
- 4 Install the fixture mounting plate with the two #6-32 screws.
- 5 Fully secure the mounting plate by screwing the anchor screws into the anchors.
- 6 Install the shade by sliding it into the brackets and secure it in place using the shade screws, washers, and nuts as shown.
- 7 Connect the fixture to a suitable ground in accordance with local electrical codes.
- 8 Connect the white fixture wire to the neutral power line with a wire nut.
- 9 Connect the black fixture wire to the hot power line with a wire nut.

Properly place the wires and wire nut connections into the junction box/fixture base, mount the fixture base onto the fixture mounting plate, and secure it in place using the fixture screws.