





# HARTLEY MEDIUM PENDANT

TFP1021

## General Product Information

Please visit [www.visualcomfort.com](http://www.visualcomfort.com) for product specs.



## Suggested/Required Tools



## Safety Information

### CAUTION-RISK OF FIRE


This product must be installed in accordance with the applicable installation code by a person familiar with the construction and operation of the product and the hazards involved.


USE MINIMUM 90°C SUPPLY CONDUCTORS.



Turn off electrical current at the source before working with any lighting fixture or portable lamp.

Install and use this product in adherence with local electrical codes and regulations.





## FIXTURE PARTS

- A. Junction box
- B. Wire Nut Connections
- C. Mounting Bar
- D. Mounting Screws
- E. Canopy Loop
- F. Canopy
- G. Collar Nut
- H. Quick Links
- I. Quick Links Chain Assembly
- J. Fixture Loop
- K. Socket Assembly
- L. Shade
- M. Shade Collar
- N. Bulb

## INSTRUCTIONS

### **I. Preparing the Fixture**

1. Secure the mounting plate to the junction box with the mounting screws.
2. Determine the desired height of the fixture and adjust the chain accordingly by doing the following:
  - a) Remove a portion of the chain by opening a link with pliers.
  - b) Install the bottom end of chain onto the fixture loop using the lower quick link.
  - c) Unscrew the collar nut from the screw collar and install it onto the chain.
  - d) Then install the canopy onto the chain and the upper quick link onto the remaining end of chain.
  - e) Secure the quick link onto the canopy loop.
3. Weaver the cord through the chain, collar nut, canopy, canopy loop, and out of the junction box.
4. Trim the cord, leaving enough length to make electrical connections.

### **II. Wiring the Fixture**

1. Safety first! Locate the circuit breaker and switch it off to cut off the power supply to the relevant circuits to ensure there's no electricity running through the wiring.
2. In accordance with local electrical codes, connect the fixture ground wire (bare copper or silver wire) to suitable ground. This may be a green ground screw on the mounting plate or a house wire (green or bare copper wire without insulation).
3. Twist the bare ends of the following pairs of wires together using a wire nut to secure a connection:
  - a) Hot fixture wire to hot power line wire
  - b) Neutral fixture wire to neutral power line wire
4. Carefully tuck all the wires behind the mounting bar into the junction box.

### **III. Installing the Fixture**

1. Place the canopy onto the mounting plate and secure it in place by screwing the collar nut tightly onto it.
2. Install the shade over the socket and secure it with the shade collar.
3. Screw the lamp into the socket to finish. Refer to the socket label for max wattage information.