



## ASSEMBLY INSTRUCTIONS

1. Carefully unpack and identify all parts referring to illustration for parts identification.
2. Turn the power to the installation point OFF.
3. Unfold the arms of the fixture body (A) to desired positions.
4. Unravel the supply power and ground wires and pass them through the rods(B), rod(C), loop (D) and canopy (E).
5. Thread the bottom of rod (B) onto the fixture body (A). Repeat the process for remaining rods(B) and rod(C) as shown in the diagram, until snug.
6. Install loop (D) onto the top of the rod (C).
7. Install the snap hooks at both ends of the bead string (H) into the small rings on the inside of the bottom of both arms. Install the snap hook at both ends of the bead string (I) into the small rings on the outside of the bottom of both arms.
8. Install the snap hook at one end of the bead string (G) into the small ring at the bottom of the fixture body (A). Install the snap hook at one end of the bead string (J) into the small ring at the bottom of the socket assembly.
9. Use carabiner (F) to connect loop (D) to the loop on the canopy (E) and twist the locking mechanism to secure.
10. Refer to the additional installation instructions included with the product for wiring and installation.
11. Install proper bulbs (not included) into each socket referring to the markings and/or labels on the fixture for maximum wattage.
12. Restore power to the installation point and retain this sheet for future reference.