



This exploded view diagram illustrates the assembly of a lighting fixture. The components are arranged vertically and horizontally to show their relative positions and assembly sequence:

- I**: A light bulb at the top.
- H**: A ring or collar component below the bulb.
- G**: A cylindrical component below the ring.
- F**: A large, ribbed cylindrical component (likely a diffuser or shade) below the cylinder.
- E**: A mounting bracket or base plate at the bottom left.
- B**: A circular component (likely a lens or reflector) to the right of the mounting bracket.
- Cx2**: Two screws used to secure the circular component B.
- Dx2**: Two screws used to secure the mounting bracket E.
- Ax3**: Three screws used to secure the circular component B to the mounting bracket E.
- Outlet Box**: A rectangular component at the bottom right, which is the base of the fixture.

Arrows indicate the direction of assembly for each component, showing how they fit together to form the complete lighting fixture.

1. Carefully unpack and identify all parts referring to illustration for parts identification.
2. Turn the power to the installation point OFF.
3. Attach the mounting plate (B) to the outlet box and secure it by using the two screws (C).
4. Connect the white wire from the fixture to the white wire of the outlet box.
Connect the black wire from the fixture to the black wire of the outlet box.
Connect the ground wire from the fixture to the ground wire of the outlet box by using the wire connectors (A) provided.
5. Install the fixture (E) onto the mounting plate (B) using side screws (D).
6. Place the shade (F) and the spacer (G) onto the socket then secure them with the socket ring (H).
7. Install the bulb (I) (not included).
8. Restore power to the installation point and retain this sheet for future reference.