1.0

Kola 13 and 22 Flush Mount

VISUAL COMFORT & CO.

MODERN COLLECTION

GENERAL PRODUCT INFORMATION:



These fixtures are intended to be installed utilizing NEC compliant junction boxes.

This product is suitable for damp locations.

This product can be dimmed with most low-voltage electronic dimmers.

This instruction shows a typical installation.

CAUTION - RISK OF FIRE

700FMKLA

This product must be installed in accordance with the applicable installation code by a person familiar with the construction and operation of the product and the hazards involved.

Use minimum 90°C supply conductors.

SAVE THESE INSTRUCTIONS!



VISUAL COMFORT & CO.

7400 Linder Ave., Skokie, IL 60077 T 847.410.4400 | F 847.410.4500 www.**visualcomfort**.com

Install the Fixture



Mark the location of the anchors and remove the mounting plate.

Line the anchor tip to the marked location and push the anchor into the ceiling up to the threads. Screw the anchor in the rest of the way with a Phillips-head screwdriver. Repeat for remaining anchor holes.

- **5** Connect the fixture to suitable ground in accordance with local electrical codes.
- 6 Connect the white driver wire to the neutral power line wire with a wire nut.
- Connect the black driver wire to the hot power line wire with a wire nut.
- Properly place the driver, all wires, and wire nut connections into the electrical box. Install the mounting plate onto the electrical box with the two #8-32 screws provided and secure it with anchor screws and washers.
- 9 Connect the black driver wire to the black fixture wire with a wire nut.
- Oconnect the red driver wire to the red fixture wire with a wire nut.
- Mount the fixture base onto the mounting plate and secure in place using the fixture screws.
- 12 Screw the shades onto the sockets.