


MILL 3-LIGHT OUTDOOR GRANDE FLOOR LAMP

VISUAL COMFORT & Co.


PRODUCT FEATURES

- Modern outdoor floor lamp with aluminum metal conical shade
- Highlights any indoor or outdoor living space, inviting an allure of coastal presence and vacation living
- Ideal for residential, hospitality and commercial applications
- Includes winterized cover
- Integrated 3-step touch-dimmer. Includes 8 feet of cloth cord
- Protected by a 5-year warranty

LAMPING



Black (On)



Black (On)

Black (On Alt 1)

Black (Off)

Black (On Alt 2)

To view all available finish options, please visit techlighting.com

ORDERING INFORMATION

SLOFL261 COLOR TEMP
27 2700K

FINISH
B BLACK

SLOFL261 _____

JOB NAME _____

NOTES _____




MILL 3-LIGHT OUTDOOR GRANDE FLOOR LAMP

VISUAL COMFORT & Co.

SPECIFICATIONS

PRIMARY MATERIAL	Stainless Steel
SHADE MATERIAL	Stainless Steel
NET WEIGHT	98.5 lbs
HEIGHT	103.9in
WIDTH	81.1in
LENGTH	81.1in
WET LISTED	
DAMP LISTED	
DRY LISTED	
GENERAL LISTING	ETL Listed
INCLUDES	



LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS		1649		
WATTS		24		
MAX WATTAGE PER BULB		24W		
		120V Integrated 3-Step Touch Dimmer		
CCT		2700K		
CRI		90 CRI		
LED LIFETIME		>60000		
L70				
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE		Integrated LED		
LAMP SHAPE		Integrated LED		
LAMP INCLUDED?		True		
WARRANTY**		5 Years		

* Dimming information available at www.techlighting.com/Downloads#dimming

** Visit techlighting.com for specific warranty limitations and details.

T20 / T24 / JA8 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6 / JA8.	No		
This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California.			

* If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.

