

KILTER WALL LIGHT



SKU: KLT-WL-DG-01-US
FINISH: DARK GREY

The Kilter Wall Light by Tala mounts flush to the wall or ceiling to create a seamless exchange with the environment. The circular aluminium shell is designed to house Tala’s Kilter S14d light sources. IP44 rated for outdoor use.



PHYSICAL

Sconce:	L 2 1/8 x W 4 2/8 x H 4 2/8in
Not used:	L - x W - x H -in
Cable length:	-
Materials:	Powder coated aluminium
Finish:	Dark Grey
Weight:	480g
IP rating:	IP44
Base:	S14D

ELECTRICAL

Appliance class	Class I
Power:	6W MAX
Voltage:	110-120V~
Frequency:	50/60Hz



DIMMING

Recommended dimmer: Lutron Diva DVELV-300P
Included Dimmer: N/A
(For a full list of recommended and compatible dimmers see website)

Tala Energy Ltd. 25b Vyner Street,
London, E2 9DG, United Kingdom

LOGISTICAL

Unit Packaging
PC/Ctn: 1
Gross weight: 680 g
L 5 7/8 x W 5 7/8 x H 3 4/8in

Tala North America, Inc., 2 Research Place,
Suite 300, Rockville, MD 20850

us.tala.co.uk | hello@tala.co.uk | +1 (240) 724-8111

WARRANTY

2 years

EAN

5060915712202

Specification subject to change without notice. Refer to our website for the most recent product documentation. Tala designs in the EU/UK are protected by registered and or unregistered design rights