

UTTERMOST

ASSEMBLY INSTRUCTIONS

21609

WARNING: TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF WHILE POWER BEFORE INSTALLING OR SERVICING THIS FIXTURE.

We suggest a licensed professional electrician for installation

Installation Steps

1. Turn power off at fuse or circuit box before starting installation process.
2. Carefully unpack your new fixture and lay out all the parts on a clear surface.
3. Choose the suitable number of stems and install the Stem-1, Stem-2 into the Coupling. Adjust the cord/wire to your desired length and remove excess.
4. Thread the Swivel (or Nipple) into the Stem-1 if needed.
5. Insert the nipple of Swivel (or Nipple) into hole in Canopy, then place the Metal washer, the lock washers over the nipple, then secure with the Hex nut.
6. Thread the Ground screw into the hole of the Circular strap. Secure the Circular strap to the outlet box with the Outlet box screws.
7. Make Wire connections with Wire Connector:
 - The smooth wire (w/ marking) from fixture to Black Wire from power source.
 - The ribbed wire (w/o marking) from Fixture to White Wire from power source.
 - Attach the Ground Wire and house ground wire to the Mounting bar with the green Ground screw.Carefully tuck wires back into the Outlet Box.
8. Place the fixture Canopy over the Circular strap, then secure with the Mounting screws.
9. Install the light bulb (Not Supplied) in accordance with the fixture's specifications. **DO NOT EXCEED THE MAXIMUM WATTAGE RATING!**
10. Slide the Glass shade over the Socket into the Cup, then secure with the Screws.

