

## McCarren Single Tier Chandelier

Item # RL 5470

### NOTICE:

This light fixture should be installed in accordance with all applicable, local installation codes, and by a person familiar with the construction and operation of it, as well as the hazards involved. Inspect item and contents carefully. If any damage or defect is found, do not install. Retain all packaging material until installation is complete and approved.

- 1. Carefully remove all parts from the carton.
- 2. Thread lamp pole (E) onto the top nipple (F) of light fixture.
- 3. Remove mounting plate (A) from base of light fixture (D) by removing base screws (C) in counter-clockwise direction.
- Affix mounting plate (A) to ceiling outlet box with mounting screws (B) provided.
- 5. Attach fixture steel safety cable to structural member in the ceiling.
- 6. Connect ground wire from the light fixture (bare copper) to ground wire (green or copper in color ), fasten together with a plastic wire connector. Tightly wrap the wire from ceiling outlet box with electrical tape. So the end of the connector is sealed. IT IS IMPERATIVE THAT THE OUTLET BOX IN YOUR HOME BE PROPERLY GROUNDED.
- Connect the hot wires (smooth wires) from the light fixture to the hot junction box wire from ceiling outlet box (usually black). Fasten together with a plastic wire connector provided and tightly wrap wire connector with electrical tape.
- Repeat the procedure with neutral wires (ribbed wire) from the light fixture to the wire from ceiling outlet box (usually white). DO NOT REVERSE THE HOT AND NEUTRAL CONNECTIONS OTHERWISE SAFETY WILL BE COMPROMISED.

# RALPH LAUREN



## McCarren Single Tier Chandelier

Item # RL 5470

### NOTICE:

This light fixture should be installed in accordance with all applicable, local installation codes, and by a person familiar with the construction and operation of it, as well as the hazards involved. Inspect item and contents carefully. If any damage or defect is found, do not install. Retain all packaging material until installation is complete and approved.

- 9. Attach fixture base (D) to the affixed mounting plate (A) and tighten with base screws (C).
- 10. Insert light bulbs into the sockets.
- Loosen thumbscrews (G), insert glass shades (J) into shade holder (H) and secure by tightening thumbscrews (G). DO NOT OVER-TIGHTEN OTHERWISE GLASS WILL BE DAMAGE.

**Care Instructions:** Clean only with a soft dry cloth or feather duster. Do not use abrasive or chemical agents.

# RALPH LAUREN