ASSEMBLY INSTRUCTIONS




Diagram 1

Varenna 19″ Pendant

Item # ARN5137

NOTICE:

This light fixture should be installed in accordance with all applicable, local installation codes, and by a person familiar with the construction and operation of it, as well as the hazards involved. Inspect item and contents carefully. If any damage or defect is found, do not install. Retain all packaging material until installation is complete and approved.

TOOLS REQUIRED (NOT INCLUDED):

Phillips Screwdriver Slotted Screwdriver Wire Strippers

Wire Cutters

---

1. Carefully remove all parts from the box. Place on a clean, soft surface.
2. Remove cover **(E)** and canopy **(K)** from mounting plate **(B)** by removing collar ring **(G)**.
3. Install mounting plate **(B)** to the junction box and secure with mounting screws **(C)**.
4. Install shade **(M)** and decorate part **(L)** to fixture **(N)** and secure with coupling **(J)**.
5. Install shade **(O)** to bottom of fixture **(N)** and secure with rod **(P)**, then install shade **(Q)** to rod **(P)** and secure with finial **(R)**.
6. Feed electrical wires through bottom rod **(I)** and connect to coupling **(J)**. Repeat for middle rod **(H)**, connecting to bottom rod **(I)**.
7. Continue feeding wires through collar ring **(F)**, cover **(E)**, canopy **(K)** and top rod **(G)**.
8. Holding fixture upright, slide collar ring **(F)**, cover **(E)** and canopy **(K)** down and rest on fixture. Then connect top rod **(G)** to middle rod **(H)**.
   NOTE: Slide components down slowly to avoid damage.
9. Hang fixture swivel ball **(D)** to the center of mounting plate **(B)**.

ASSEMBLY INSTRUCTIONS




Diagram 1

Varenna 19″ Pendant

Item # ARN5137

NOTICE:

This light fixture should be installed in accordance with all applicable, local installation codes, and by a person familiar with the construction and operation of it, as well as the hazards involved. Inspect item and contents carefully. If any damage or defect is found, do not install. Retain all packaging material until installation is complete and approved.

---

10. Cut excess wires, being sure to leave enough to reach the junction box. Separate wires and strip insulation on each 5/8”.
11. Wrap fixture ground wire (bare copper) around the green grounding screw (see diagram 1). Tighten. Continue fixture ground wire and connect to supply ground wire (usually green or bare copper) using wire nut **(A)**.
    NOTE: It is imperative that the fixture is grounded.
12. Connect fixture neutral wire (white) to the supply neutral wire (usually white) using wire nut **(A)**.
13. Connect fixture hot wire (black) to the supply hot wire (usually black) using wire nut **(A)**.
    CAUTION: Do not reverse the hot and neutral connections.
14. Make sure all wire connections are tight, then carefully tuck into the junction box.
15. Install cover **(E)** and canopy **(K)** to mounting plate **(B)** and secure with collar ring **(F)**.
16. Install light bulbs into the sockets.

CARE INSTRUCTIONS: Clean only with a soft dry cloth or feather duster. Do not use abrasive or chemical agents.