


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:12.939V I:1.8906A P:24.264W PF:0.9919 Freq:60.00Hz UTHDi:0.00% ITHDi:0.00% Lamp Flux:1159.13lm


NAME: 5812-CSBZ-C-MAX	TYPE: Landscape Lighting	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: WAC Lighting	SUR.: 0.005	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 47.77 lm/W
MODEL		Imax(cd)	827.2	S/MH(C0/180)	1.03	
NOMINAL POWER(W)		LOR(%)	100.0	S/MH(C90/270)	1.12	
RATED VOLTAGE(V)	12	TOTAL FLUX(lm)	1159.1	η UP,DN(C0-180)	0.0,48.8	
NOMINAL FLUX(lm)	1159.13	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.0,51.1	
LAMPS INSIDE	1	η up(%)	0.1	CIBSE SHR NOM	1.00	
TEST VOLTAGE(V)	12	η down(%)	99.9	CIBSE SHR MAX	1.15	

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: Oliver
Test Date: 2023-09-28

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-R5000_V2 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 2.482m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM


ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	$\%lum$
10	826.8	826.2	823.7	821.8	820.7	819.0	819.8	824.1	0- 10	78.59	78.59	6.78
20	783.7	781.8	770.9	757.9	748.0	753.1	766.9	781.6	10- 20	226.8	305.4	26.3
30	653.3	626.6	584.5	548.4	549.9	589.0	629.5	670.0	20- 30	320.0	625.4	54
40	414.0	363.7	299.4	254.8	271.3	323.5	382.0	433.1	30- 40	297.9	923.4	79.7
50	136.0	115.5	80.54	67.75	72.65	92.39	123.3	143.6	40- 50	160.2	1084	93.5
60	31.51	28.84	24.20	22.18	22.80	25.74	30.13	33.11	50- 60	48.77	1132	97.7
70	12.15	11.53	10.14	9.399	9.886	10.58	11.57	12.33	60- 70	17.64	1150	99.2
80	3.368	3.164	2.749	2.561	2.975	3.132	3.411	3.672	70- 80	6.918	1157	99.8
90	0.0128	0.0126	0.0116	0.0134	0.0072	0.0081	0.0115	0.0242	80- 90	1.308	1158	99.9
100	0.0204	0.0260	0.0256	0.0265	0.0111	0.0115	0.0090	0.0107	90-100	0.0137	1158	99.9
110	0.0267	0.0332	0.0337	0.0343	0.0281	0.0251	0.0218	0.0193	100-110	0.0225	1158	99.9
120	0.0526	0.0545	0.0662	0.0672	0.1100	0.0945	0.0768	0.0709	110-120	0.0474	1158	99.9
130	0.1055	0.1132	0.1268	0.1301	0.2225	0.2097	0.1932	0.1821	120-130	0.0998	1158	99.9
140	0.1822	0.1956	0.2102	0.2134	0.3518	0.3413	0.3225	0.3075	130-140	0.1650	1159	100
150	0.2833	0.2978	0.3122	0.3131	0.4650	0.4599	0.4428	0.4259	140-150	0.1994	1159	100
160	0.3648	0.3762	0.3840	0.3829	0.5409	0.5415	0.5319	0.5122	150-160	0.1914	1159	100
170	0.4264	0.4371	0.4434	0.4368	0.5353	0.5377	0.5374	0.5285	160-170	0.1338	1159	100
180	0.5162	0.5198	0.5213	0.5154	0.5094	0.5155	0.5182	0.5126	170-180	0.0475	1159	100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:Oliver
 Test Date:2023-09-28

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 γ Test System:EVERFINE GO-R5000_V2 SYSTEM V2.00.428
 Humidity:65.0%
 Test Distance:2.482m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Oliver
Test Date:2023-09-28

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-R5000_V2 SYSTEM V2.00.428
Humidity:65.0%
Test Distance:2.482m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)									
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	.00
1.0	1.09	1.07	1.04	1.07	1.05	1.02	1.03	1.01	.99	.99	.98	.96	.96	.95	.93	.92
2.0	1.00	.96	.92	.99	.94	.91	.95	.92	.89	.92	.89	.87	.89	.87	.85	.83
3.0	.92	.86	.82	.91	.85	.81	.88	.83	.80	.85	.82	.78	.83	.80	.77	.75
4.0	.85	.78	.73	.84	.78	.73	.81	.76	.72	.79	.75	.71	.77	.73	.70	.69
5.0	.78	.71	.66	.77	.71	.66	.75	.70	.66	.73	.69	.65	.72	.68	.64	.63
6.0	.72	.65	.60	.71	.65	.60	.70	.64	.60	.68	.63	.59	.67	.62	.59	.57
7.0	.67	.60	.55	.66	.60	.55	.65	.59	.55	.64	.58	.55	.62	.58	.54	.53
8.0	.62	.56	.51	.62	.55	.51	.61	.55	.51	.59	.54	.50	.58	.54	.50	.48
9.0	.58	.51	.47	.58	.51	.47	.57	.51	.47	.56	.50	.46	.55	.50	.46	.45
10.0	.54	.48	.44	.54	.48	.43	.53	.47	.43	.52	.47	.43	.51	.47	.43	.42



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: Oliver
Test Date: 2023-09-28

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-R5000_V2 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 2.482m [K=1.0000]
Remarks:

WEC AND CCEC

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.203	.116	.037	.196	.112	.036	.184	.105	.034	.172	.099	.032	.161	.093	.030	
2.0	.197	.108	.033	.191	.105	.032	.180	.100	.031	.170	.096	.030	.161	.091	.029	
3.0	.188	.100	.030	.183	.098	.030	.174	.094	.029	.165	.091	.028	.157	.087	.027	
4.0	.180	.093	.027	.175	.092	.027	.167	.089	.026	.159	.086	.026	.152	.083	.025	
5.0	.171	.087	.025	.167	.086	.025	.160	.083	.025	.153	.081	.024	.147	.078	.024	
6.0	.163	.082	.023	.159	.080	.023	.153	.078	.023	.147	.076	.022	.141	.074	.022	
7.0	.155	.077	.022	.152	.076	.022	.146	.074	.021	.141	.072	.021	.136	.071	.021	
8.0	.148	.072	.020	.145	.071	.020	.140	.070	.020	.135	.068	.020	.131	.067	.020	
9.0	.141	.068	.019	.139	.068	.019	.134	.066	.019	.130	.065	.019	.125	.064	.018	
10.0	.135	.065	.018	.132	.064	.018	.128	.063	.018	.124	.062	.018	.121	.061	.017	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Ceiling Cavity Exitance Coefficients(CCEC)												
0.0	.191	.191	.191	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.174	.158	.143	.148	.135	.123	.102	.093	.085	.058	.054	.050	.019	.017	.016	
2.0	.160	.133	.110	.137	.114	.095	.094	.079	.066	.054	.046	.039	.017	.015	.013	
3.0	.149	.114	.086	.128	.099	.075	.088	.069	.053	.051	.040	.031	.016	.013	.010	
4.0	.140	.100	.069	.120	.086	.060	.083	.060	.042	.048	.035	.025	.015	.011	.008	
5.0	.132	.089	.057	.114	.077	.049	.078	.054	.035	.045	.032	.021	.015	.010	.007	
6.0	.126	.080	.047	.108	.069	.041	.074	.048	.029	.043	.028	.017	.014	.009	.006	
7.0	.119	.073	.040	.103	.063	.035	.071	.044	.025	.041	.026	.015	.013	.009	.005	
8.0	.114	.067	.034	.098	.058	.030	.068	.041	.021	.039	.024	.013	.013	.008	.004	
9.0	.109	.062	.030	.094	.053	.026	.065	.038	.018	.038	.022	.011	.012	.007	.004	
10.0	.104	.057	.026	.090	.050	.023	.062	.035	.016	.036	.021	.010	.012	.007	.003	

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: Oliver
 Test Date: 2023-09-28

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-R5000_V2 SYSTEM V2.00.428
 Humidity: 65.0%
 Test Distance: 2.482m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	23.8	24.9	24.0	25.1	25.3	22.6	23.7	22.8	23.9	24.1
3H	23.7	24.7	24.0	24.9	25.2	22.5	23.5	22.8	23.7	24.0
4H	23.7	24.6	23.9	24.9	25.1	22.5	23.4	22.7	23.6	23.9
6H	23.6	24.5	23.9	24.7	25.0	22.4	23.3	22.7	23.5	23.8
8H	23.5	24.4	23.9	24.7	24.9	22.3	23.2	22.7	23.5	23.7
12H	23.5	24.3	23.8	24.6	24.9	22.3	23.1	22.6	23.4	23.7
4H 2H	23.6	24.6	23.9	24.8	25.0	22.4	23.4	22.7	23.6	23.9
3H	23.6	24.4	23.9	24.7	24.9	22.4	23.2	22.7	23.5	23.8
4H	23.5	24.3	23.9	24.6	24.9	22.4	23.1	22.7	23.4	23.7
6H	23.5	24.1	23.8	24.4	24.8	22.3	23.0	22.7	23.3	23.6
8H	23.4	24.0	23.8	24.4	24.7	22.3	22.9	22.7	23.2	23.6
12H	23.4	23.9	23.8	24.3	24.7	22.2	22.8	22.6	23.1	23.5
8H 4H	23.4	24.0	23.8	24.4	24.7	22.2	22.9	22.6	23.2	23.6
6H	23.3	23.8	23.8	24.2	24.7	22.2	22.7	22.6	23.1	23.5
8H	23.3	23.7	23.8	24.2	24.6	22.2	22.6	22.6	23.0	23.5
12H	23.3	23.6	23.7	24.1	24.6	22.1	22.5	22.6	22.9	23.4
12H 4H	23.3	23.9	23.8	24.3	24.7	22.2	22.8	22.6	23.1	23.5
6H	23.3	23.7	23.8	24.2	24.6	22.2	22.6	22.6	23.0	23.5
8H	23.3	23.6	23.7	24.1	24.6	22.1	22.5	22.6	22.9	23.4
Variations with the observer position at spacings(CIE Pub.117):										
S = 1.0H	+ 2.2 / - 5.5					+ 2.2 / - 5.8				
1.5H	+ 3.2 / - 5.0					+ 3.1 / - 4.5				
2.0H	+ 5.5 / - 5.2					+ 4.6 / - 4.0				

CIE Pub.117, 1159 lm Total Lamp Luminous Flux Corrected ($8\log(F/F_0) = 0.5$)

Area: 0.005 m2

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:Oliver
 Test Date:2023-09-28

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-R5000_V2 SYSTEM V2.00.428
 Humidity:65.0%
 Test Distance:2.482m [K=1.0000]
 Remarks:


UTILIZATION FACTORS TABLE

REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	79	71	66	78	71	66	77	70	66	61
0.80	87	80	75	87	80	75	85	79	75	70
1.00	94	87	82	93	86	82	91	86	81	77
1.25	99	92	88	97	92	88	95	90	87	82
1.50	102	96	92	101	95	92	98	94	90	85
2.00	106	101	97	104	100	96	101	98	95	89
2.50	108	103	100	106	102	99	103	100	97	91
3.00	110	106	103	108	104	101	104	102	99	92
4.00	112	109	106	110	107	105	106	104	102	95
5.00	114	111	108	111	109	107	107	105	104	96
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004				Suspended				SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: Oliver
 Test Date: 2023-09-28

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-R5000_V2 SYSTEM V2.00.428
 Humidity: 65.0%
 Test Distance: 2.482m [K=1.0000]
 Remarks:


ISOCANDELA DIAGRAM



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: Oliver
Test Date: 2023-09-28

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-R5000_V2 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 2.482m [K=1.0000]
Remarks:


AAI Figure



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: Oliver
 Test Date: 2023-09-28

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-R5000_V2 SYSTEM V2.00.428
 Humidity: 65.0%
 Test Distance: 2.482m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: Oliver
Test Date: 2023-09-28

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-R5000_V2 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 2.482m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:12.939V I:1.8906A P:24.264W PF:0.9919 Freq:60.00Hz UTHDi:0.00% ITHDi:0.00% Lamp Flux:1159.13x1 lm

NAME: 5812-CSBZ-C-MAX	TYPE: Landscape Lighting	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: WAC Lighting	SUR.: 0.005	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	8143
L_0~180(75)av	4937
L_0~180(85)av	2456
L_90~270(65)av	8106
L_90~270(75)av	4858
L_90~270(85)av	2333
L_45(65)av	8176
L_45(75)av	4907
L_45(85)av	2402

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:Oliver
 Test Date:2023-09-28

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-R5000_V2 SYSTEM V2.00.428
 Humidity:65.0%
 Test Distance:2.482m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: Oliver
Test Date: 2023-09-28

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-R5000_V2 SYSTEM V2.00.428
Humidity: 65.0%
Test Distance: 2.482m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Table--1

UNIT: cd

C(DEG) γ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	822	822	822	822	822	822	822	822	822	822	822	822	822	822	822	822			
5	825	825	824	823	823	823	823	823	823	823	823	822	822	822	823	824			
10	827	827	826	824	824	822	822	821	821	819	819	818	820	821	824	826			
15	816	816	815	813	811	808	805	800	799	797	798	799	804	808	812	815			
20	784	784	782	776	771	764	758	749	748	749	753	760	767	775	782	785			
25	730	726	720	708	696	684	671	662	664	672	685	699	709	723	735	736			
30	653	639	627	604	585	564	548	541	550	566	589	612	629	650	670	668			
35	550	525	506	473	448	419	400	397	414	436	466	493	520	545	570	569			
40	414	384	364	326	299	270	255	251	271	294	323	350	382	406	433	430			
45	263	240	222	190	167	148	138	137	149	164	188	211	237	256	277	274			
50	136	125	115	97.0	80.5	72.1	67.8	67.0	72.6	79.3	92.4	108	123	135	144	144			
55	62.1	58.7	53.4	46.1	40.2	37.4	35.6	34.9	37.2	39.3	44.4	51.4	57.7	63.2	66.0	66.9			
60	31.5	30.7	28.8	26.3	24.2	23.1	22.2	21.7	22.8	23.5	25.7	28.3	30.1	32.2	33.1	33.8			
65	19.2	19.0	18.2	17.0	15.9	15.2	14.7	14.5	15.2	15.5	16.5	17.5	18.3	19.2	19.7	20.1			
70	12.2	12.0	11.5	10.8	10.1	9.66	9.40	9.29	9.89	10.0	10.6	11.1	11.6	12.0	12.3	12.6			
75	6.95	6.84	6.63	6.19	5.81	5.52	5.36	5.32	5.82	5.90	6.20	6.48	6.77	6.98	7.21	7.39			
80	3.37	3.27	3.16	2.94	2.75	2.62	2.56	2.54	2.97	3.01	3.13	3.26	3.41	3.54	3.67	3.78			
85	1.19	1.12	1.07	0.98	0.93	0.88	0.87	0.86	0.95	0.96	0.99	1.03	1.11	1.18	1.26	1.30			
90	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.02	0.02	0.03		
95	0.01	0.01	0.02	0.02	0.02	0.02	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01			
100	0.02	0.02	0.03	0.03	0.03	0.03	0.03	0.02	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01			
105	0.02	0.02	0.03	0.03	0.03	0.03	0.03	0.03	0.02	0.02	0.02	0.01	0.01	0.01	0.01	0.01			
110	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.02	0.02	0.02	0.02	0.02			
115	0.04	0.04	0.04	0.04	0.05	0.05	0.05	0.05	0.06	0.06	0.05	0.05	0.05	0.04	0.04	0.04			
120	0.05	0.05	0.05	0.06	0.07	0.07	0.07	0.06	0.11	0.10	0.09	0.09	0.08	0.07	0.07	0.07			
125	0.07	0.07	0.08	0.08	0.09	0.09	0.09	0.09	0.15	0.15	0.14	0.13	0.13	0.12	0.12	0.12			
130	0.11	0.11	0.11	0.12	0.13	0.13	0.13	0.13	0.22	0.22	0.21	0.20	0.19	0.19	0.18	0.18			
135	0.15	0.15	0.16	0.17	0.18	0.18	0.18	0.18	0.29	0.29	0.28	0.27	0.26	0.25	0.25	0.25			
140	0.18	0.19	0.20	0.20	0.21	0.21	0.21	0.21	0.35	0.35	0.34	0.33	0.32	0.31	0.31	0.31			
145	0.23	0.24	0.24	0.25	0.26	0.26	0.26	0.26	0.41	0.41	0.40	0.39	0.38	0.37	0.37	0.37			
150	0.28	0.29	0.30	0.31	0.31	0.31	0.31	0.31	0.46	0.46	0.46	0.45	0.44	0.43	0.43	0.42			
155	0.33	0.33	0.34	0.35	0.35	0.35	0.35	0.35	0.51	0.51	0.50	0.50	0.49	0.48	0.47	0.47			
160	0.36	0.37	0.38	0.38	0.38	0.38	0.38	0.38	0.54	0.54	0.54	0.54	0.53	0.52	0.51	0.50			
165	0.40	0.40	0.41	0.41	0.41	0.41	0.41	0.40	0.55	0.55	0.55	0.55	0.55	0.54	0.53	0.53			
170	0.43	0.43	0.44	0.44	0.44	0.44	0.44	0.43	0.54	0.54	0.54	0.54	0.54	0.53	0.53	0.52			
175	0.48	0.49	0.49	0.49	0.49	0.49	0.49	0.48	0.53	0.54	0.54	0.54	0.53	0.53	0.53	0.52			
180	0.52	0.52	0.52	0.52	0.52	0.52	0.52	0.50	0.51	0.51	0.52	0.52	0.52	0.51	0.51	0.51			

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: Oliver
 Test Date: 2023-09-28

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-R5000_V2 SYSTEM V2.00.428
 Humidity: 65.0%
 Test Distance: 2.482m [K=1.0000]
 Remarks: