


12VAC LANDSCAPE OUTDOOR TAPE

Wet Rated LED Tape

WAC

LANDSCAPE LIGHTING



PRODUCT DESCRIPTION

A high-performance, durable lighting solution. It integrates smoothly with standard transformers, offering dot-free, COB technology illumination. Energy-efficient at only 1.5W per foot, it provides 100 lumens per foot with a 90+ color rendering index. This UV-stabilized, IP66-rated strip is ideal for any setting, including water features. Easy to install with push-in connectors and cuttable for custom lengths, it's available in 2700K and 3000K warm white tones. Safe for wet locations and long-lasting with a 50,000-hour lifespan, this strip is perfect for creating inviting and efficient outdoor lighting.

FEATURES

- Seamless integration with standard magnetic transformers for landscape lighting
- COB technology ensures uniform, dot-free illumination
- Constructed with double-insulated, UV-stabilized silicone for durability
- Energy-efficient, consuming only 1.5W per foot while delivering 100 lumens per foot
- High color fidelity with a 90+ color rendering index
- IP66 rated, suitable for water feature applications
- Easy-to-use push-in connectors for simple, hassle-free installation
- Available in warm white tones of 2700K and 3000K
- Cuttable every 2 inches with end-caps to maintain integrity
- Versatile spool lengths: 1ft, 5ft, 10ft, 20ft, and 35ft
- Compatible with MLV dimmers for adjustable brightness
- cULus Listed, certified safe for outdoor wet locations
- Long-lasting with a rated life of 50,000 hours

ORDERING NUMBER

		Color Temp		Finish	
8012	1 foot	27	2700K	WT	White
8052	5 feet				
8102	10 feet				
8202	20 feet				
8235	35 feet				
		30	3000K		

- **WT**

Example: **8012-30WT**

Fixture Type:

Catalog Number:

Project:

Location:

SPECIFICATIONS

Input:	9-15VAC (Transformer is required)
Power:	1.5 W/ft
Brightness:	100 lm/ft
CRI:	90+
Rated Life:	50,000 hours
Operating Temp:	4°F to 104°F (-20°C to 40°C) at relative humidity 95%

Total Length of Lead Wire Between Magnetic Transformer and Tape	Max Run Length
	With 5A Fuse Lead Wire
6 ft	35 ft
9 ft	35 ft
12 ft	27 ft
18 ft	18 ft
24 ft	13 ft
30 ft	10 ft
40 ft	8 ft

wacighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters, East Manufacturing Facility

44 Harbor Park Drive

Port Washington, NY 11050

South East Manufacturing Facility

1600 Distribution Ct

Lithia Springs, GA 30122

Central Manufacturing Facility

1700 South J Elmer Freeway, Ste 100

Cedar Hill, TX 75104

West Manufacturing Facility

1750 S Archibald Ave

Ontario, CA 91761

12VAC LANDSCAPE OUTDOOR TAPE

Wet Rated LED Tape

WAC

LANDSCAPE LIGHTING

Clear channel



T24-OD-CH5-CL

5 feet

Includes mounting hardware

End cap



T24-OD-EC-WT

Surface mounting clip



T24-OD-C1-WT

Secures on both edges
(10 Qty)

Edge mounting clip



T24-OD-C2-WT

Secures on one edge
(10 Qty)

Invisible clip



T24-OD-C3-WT

Spring clip secures
beneath tape (10 Qty)

Lead wire with 5A fuse
35 ft max tape run



Protects tape sections
from over current

8002-06WT

6 feet

8002-10WT

10 feet

Joiner Cable - Short



T24-OD-IC6-WT

6 inch

T24-OD-IC12-WT

1 foot

Joiner Cable - Long



T24-OD-IC72-WT

6 feet

T24-OD-IC120-WT

10 feet

4 Way "X" Connector



T24-OD-X-WT

3 Way "Y" Connector



T24-OD-Y-WT

Magnetic Transformers

Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed
See transformer spec sheet for details and its accessories

9075-TRN-SS

75W Max

9150-TRN-SS

150W Max

9300-TRN-SS

300W Max

9600-TRN-SS

600W Max



waclighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters, East Manufacturing Facility

44 Harbor Park Drive

Port Washington, NY 11050

South East Manufacturing Facility

1600 Distribution Ct

Lithia Springs, GA 30122

Central Manufacturing Facility

1700 South J Elmer Freeway, Ste 100

Cedar Hill, TX 75104

West Manufacturing Facility

1750 S Archibald Ave

Ontario, CA 91761