


SWIRL 5

F-105L

56" Ceiling Fan

WAC
SMART FANS



PRODUCT DESCRIPTION

Sensual and intriguing, the SWIRL 5 Smart Fan by WAC is highlighted with a unique blade shape and design. This Energy Star rated creates a unique impression with the stunning geometric five-blade design while offering comfortable air circulation throughout your home.

FEATURES

- 6 fan speeds through both Summer and Winter Modes
- Silent DC motor
- Luminaire cover not included
- Includes remote control with wall cradle (RC20-WT)
- Wall control for 3, 4-way control sold separately
- Compatible with WAC Smart Fans app

AIRFLOW/ENERGY EFFICIENCY

| | |
|---|-----------|
| Weighted-Average/High Airflow CFM: | 4439/6408 |
| Weighted-Average/High Energy Use (W): | 27/38 |
| Estimated Yearly Energy Cost (\$): | 8 |
| Weighted-Average/High Efficiency (CFM/W): | 188 |
| Max RPM: | 111 |

ORDER NUMBER

| Model | Housing | Blade |
|--------|-----------------------|--------------------------|
| F-105L | MB <i>Matte Black</i> | DK <i>Distressed Koa</i> |
| | MB <i>Matte Black</i> | MB <i>Matte Black</i> |

F-105L-__

Example: F-105L-MB/DK

*This fan comes uni-pack - blade select options are not available

* Range results may vary based on application and surroundings.

SPECIFICATIONS

| | |
|-----------------|--|
| Construction: | Aluminum, ABS |
| Blade: | 24° Pitch, 56" sweep |
| Downrod: | 3/4"W X 6"H included |
| Mounting Slope: | Up to 30° |
| Wire: | 80" |
| Hanging Weight: | 17 lbs |
| Total Power: | 59W |
| Standards: | UL/cUL Wet Location listed, Title 24 JA8-2016, Title 20, Energy Star |
| Motor Type: | DC 120 x D-15 |

WIRELESS PERFORMANCE

| | |
|------------------|---------------|
| Wi-Fi Range: | Up to 150 ft* |
| Bluetooth Range: | Up to 150 ft* |

LUMINAIRE PERFORMANCE

| | |
|--------------------------|---------------------------------------|
| Light Source: | LED |
| Light Wattage: | 21W |
| Lumens/Delivered: | 1991 - 2159 (Based on CCT)/1228 |
| Dimming: | Integrated |
| CRI: | 90 |
| Color Temperature: Rated | 2700K, 3000K, 4000K, 5000K selectable |
| Life: | 50,000 hours |

The WAC app synchronizes seamlessly with smart home devices you already own



wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

WAC retains the right to modify the design of our products at any time as part of the company's continuous improvement program. October 2021






SWIRL 5

F-105L

56" Ceiling Fan

WAC
SMART FANS

OPTIONAL ACCESSORIES

| | | | | |
|--------------------------|---|---|-----------------------|---|
| Bluetooth Wall Control |  | WC20- | WT White | Control fan speed and light brightness, and switch between Summer and Winter Modes. Additional Wall Controls can be purchased separately for multiple location control. |
| Bluetooth Remote Control |  | RC20- | WT White | Control fan speed and light brightness, and switch between Summer and Winter Modes. Compatible with WAC Smart Fans. Includes easy-to-install wall cradle and batteries. |
| Downrod |  | DR12- 12IN DR18- 18IN DR24- 24IN DR36- 36IN DR48- 48IN DR60- 60IN DR72- 72IN | MB Matte Black | All our downrods are .75 (in) and are threaded on the motor end to create an extra layer of security and allow for adjustments in the field. |
| Downrod Couplers |  | DC- | | Connects two downrods together. |
| Sloped Ceiling Kit |  | SC- | | Designed to accommodate buildings with steeper sloped ceilings up to 45o or 12/12 pitch. |

Examples: Wall Control - **WC20-WT**, Remote Control - **RC20-WT**, Downrod - **DR12-MB**, Downrod Coupler - **DC-MB**, Sloped Ceiling Kit - **SC-MB**

SUGGESTED DOWNROD HEIGHT USAGE

| Ceiling Height | 15' | 14' | 13' | 12' | 11' | 10' | 9' |
|----------------|-----|-----|-----|-----|-----|-----|-----|
| Downrod | 72" | 60" | 48" | 36" | 24" | 18" | 12" |

SLOPED CEILING DEGREE CONVERSION CHART

| Degree | 4-8° | 9-13o | 14-17o | 18-21o | 22-25o | 26-29o | 30-32o | 33-35o | 36-38o | 39-41o | 42-44o | 45o |
|---------------|-------|-------|--------|--------|--------|--------|--------|--------|--------|--------|--------|-------|
| Ceiling Slope | 1/12 | 2/12 | 3/12 | 4/12 | 5/12 | 6/12 | 7/12 | 8/12 | 9/12 | 10/12 | 11/12 | 12/12 |
| Pitch | pitch | pitch | pitch | pitch | pitch | pitch | pitch | pitch | pitch | pitch | pitch | pitch |

Supplied mounting brackets allow mounting on ceiling slopes up to 30° (7/12 pitch). Optional slope kit allows mounting on ceilings up to 45° (12/12 pitch). The receiver will mount inside canopy up to 45°.

NOTE: Recommended maximum downrod length of 72" with 80" lead wire

WAC retains the right to modify the design of our products at any time as part of the company's continuous improvement program. October 2021