

COLLAGE 450/600

Designed by Louise Campbell



Description

The fixture emits diffused light directed primarily downwards. The patterns on the three laser cut acrylic shades have been carefully staggered with the aim of eliminating unpleasant glare from the light source. The patterns differ between the shades, resulting in different perceptions of light and shadow depending on the viewing angle.

Variants

VARIANT NUMBER	COLOR, RAL	W / H / L (IN) / W (LB)
5741928679	WHITE, 31	17.7 / 11 / 17.7 IN / 7.4 LB
5741928682	WHITE, 31	23.6 / 14.2 / 23.6 IN / 10.2 LB

Materials & Finishes

MATERIALS

Suspension: Naturally anodized aluminum. Shades: Laser cut acrylic.

FINISHES

White matte.

louis poulsen

Mounting


Canopy: White. Cord type: 3-conductor, 18 AWG white PVC power cord. Cord length: 12'.
For mounting instructions, see download section on the product detail page.

Information


Electrical:
System Wattage: 22W
LED Wattage: 20 W
Delivered lumens: 1,625
Efficacy: 73.9 lm/W
Certifications:
cULus, Dry Location
Protection class IP20
Controllability: Phase dimming
Actual performance dependent upon screw-base lamp used. For the E-socket product variants, bulbs are not included. LED light source is part of the product.

Light distribution diagrams


CARTESIAN



ISOLUX



POLAR



Variant Options

For particular variant options, please check our online Product Variants Configurator on the product detail page.

VARIANT NO.	LIGHT SOURCE	VOLTAGE/FRQ	LUMEN	FEATURES	CABLE
5741928679	A-21/medium	120V	1625	-	White textile
5741928682	A-21/medium	120V	1625	-	White textile